


LED Floodlight

SLIM FLOODPAK VI


High Efficiency with Meanwell Driver

Variable Mounting Positions





Ceiling Installation



Dimension (mm)						
Power	A	В	С			
100W	308	265	65			
150W	348	308	65			
200W	383	347	65			
250W	430	385	65			



FEATURES

- High Power Philips LED Chip
- Reliable Meanwell Driver
- Easy installation with different mounting positions like Ceiling, Ground & Wall
- System Efficacy upto 130 lm/W
- · Lifespan of 50,000 Hours
- Switching cycle >100,000 times
- Warranty 5 Years product replacement

APPLICATIONS

- Park Lighting
- Playground & Stadium
- Landscape Lighting
 Exhibition Hall
- Advertising Lighting
 Warehouse

SPECIFICATIONS

SKU	21495	21496	21497	21498
Power	100W*	150W	200W*	250W*
Lumen(lm)	13000	19500	26000	32500
сст (к)	6000	6000	6000	6000
Rating	IP65	IP65	IP65	IP65
PF	0.9	0.9	0.9	0.9
CRI	≥ 80	≥ 80	≥ 80	≥ 80
Beam Angle	120°	120°	120°	120°
IK Rating	08	08	08	08

Other wattages are available on indent basis



